

METAL ROOFING

STANDING SEAM METAL PANS



Custom made any length
 Over 30 colors available
 24 Gauge Steel
 16 oz Copper
 Lead Coated Copper
 Terne II

Forming Speed. 50 ft./min.
 Maximum Sheet Width. 28"
 Minimum Sheet Width. 16"
 Max. Steel Gauge. 24 GA
 Min. Steel Gauge. 30 GA
 Max. Aluminum Gauge.032
 Max. Copper Gauge. 20 oz.

In addition to traditional standing seam roofing panels, J&L is now offering east to install "Snap Lock" panels. The hidden mechanism on these panels eliminates the need for field seams. They are installed with concealed cleats, or they can be created with a nailing hem for even faster installation.



METAL ROOFING

TAMKO METALWORKS®

STONECREST TILE™



- Distinctive look of smooth, uniform tile.
- 50 Year Limited Warranty
- Energy Star Qualified Cool Colors
- Highly reflective to help lower energy costs
- Lightweight compared to traditional roofing products

COPPER SHEETS AND ROLLS

AMERICAN BRASS

COLD ROLLED COPPER
SOFT COPPER ROLL
RIDGE ROLL COPPER
LEAD COATED COPPER
COPPER SHEET
COPPER RIDGE ROLL
COPPER CLAD STAINLESS
(Please call for details)



ATAS ACCEL ROOFING PRODUCTS


ADVANTA

- 29ga Steel
- A steep slope, non-structural shingle.
- An alternative to traditional asphalt shingle.
- Coverage Width: 12"
- Coverage Length: 36"
- Choice of 8 standard, and 6 designer colors (Americana Series), with KYNAR 500® or HYLAR 5000® finish



PERMASHAKE™

- .032 Aluminum, 29ga Steel
- A steep slope, non-structural shingle.
- Simulates the look of wood grained shingles.
- Width: 10"
- Length: 60"



CASTLETOP®

- .028 Zinc, .032 Aluminum, 16oz Copper
- Steep slope, non-structural shingle.
- Diamond shaped metal shingle.
- Size of the shingle is 15-3/4" x 15-3/4".
- Actual exposure is 13-1/2" x 13-1/2".



BERMUDA PANEL RUMBA SHAKE

- .032 Aluminum, 16oz Copper, 24ga 55% Al/Zn coated steel with clear acrylic coating, 24ga Galvanized Steel
- A steep slope, non-structural shingle.
- A Bermuda style roof panel.
- Width: 9"
- Length: 2'-0" minimum, 12'-0" standard, or 20'-0" maximum
- Choice of 29 standard colors, with KYNAR 500® or HYLAR 5000® finish.
- Special offerings: anodized Aluminum, clear or bronze, and 16 oz. Copper

STANDING SEAM SHINGLE

- 16oz Copper, 29ga Steel
- A steep slope, non-structural shingle.
- Antique style standing seam.
- Width: 16"
- Length: 36" or 60"



Trim pieces include: eave trim, gable trim, J channels, fascia, hip and ridge caps and valley trims. (Call for details)

INVARIMATTE

INVARIMATTE

- No-directional, low gloss, uniformly textured finish.
- Can be
 - Used in roofing, flashing, and wall panels
 - Soldered or welded in as shipped condition
 - Field painted to assure historical accuracy