

J&L Building Materials, Inc.

Natural Slate & Cedar Roofing



SLATE

NORTH COUNTRY NATURAL SLATE

NORTH COUNTRY SLATE

Standards	3/16-1/4"	650-800lbs/square
Quarters	¼-3/8"	800-1200 lbs/square
Heavies	3/8-1/2"	200-1800lbs/square
Extra Heavies	½-3/4"	1800-2500 lbs./square

- Grade: ASTM C 406 Grade S1: Expected service life 75+ years
- Grade: ASTM C 406 Grade S2: Expected service life 40-75 years
- Grade ASTM C 406 Grade S3: Expected service life 20-40 years
- Thickness: Standards- Nominal 3/16 inch to ¼ inch
- Thickness: Quarters- Nominal ¼" to 3/8 inch
- Thickness: Heavies- Nominal 3/8" to ½"
- Thickness: Extra Heavies- Nominal ½" to 3/4"

CEDAR ROOFING

RED CEDAR

- 18" #1 Perfection
- 18" 5/8" Tapersawns Pressure Treated
- 18" ¾" Heavy Tapersawns
- 18" 7/8" Heavy Tapersawns
- 18" 7/8" Heavy Tapersawns Pressure Treated
- 24" Royals
- 24" Royals Pressure Treated
- 24" 7/8" Heavy Tapersawns
- 24" 7/8" Tapersawn Pressure Treated
- 24" 5/8" Tapersawn
- 5/8" Premade Hip/Ridge 16ft
- Premade Hip/Ridge 16ft Pressure Treated
- ¾" Premade Hip Ridge 16ft
- ¾" Premade Hand Split Hip/Ridge
- 24" #1 Medium Hand Split
- 24" Premium Heavy Hand Splits
- Additional Cedar Roofing products available
- Call for size, pricing, and availability

Disclaimer

Although the information and recommendations in this document are presented in good faith, J&L Building Materials makes no warranties as to the completeness or accuracy.